

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	860
1	14/0.3	16	1190
1.5	22/0.3	12	1715
2.5	50/0.25	8	2780
4	56/0.3	6	4215
6	84/0.3	4	6205

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.50	180	1170
0.75	24/0.2	8	9.39	180	1690
1	32/0.2	13	12.06	180	2170
1.5	30/0.25	17	17.64	180	3175
2.5	50/0.25	24	28.58	180	5145
4	56/0.3	30	45.31	180	8155
6	84/0.3	38	66.72	180	12010
10	140/0.3	52	114.80	100	11480
16	126/0.4	70	182.50	100	18250
25	196/0.4	88	283.50	100	28350
35	276/0.4	112	396.80	100	39680
50	396/0.4	146	569.00	100	56900
70	360/0.5	216	828.15	100	82815
95	480/0.5	262	1073.30	100	107330
120	608/0.5	310	1368.80	100	136880
150	750/0.5	355	1707.40	100	170740
185	931/0.5	415	2078.35	100	207835
240	1200/0.5	500	2748.85	100	274885
300	1500/0.5	550	3432.25	100	343225
400	2013/0.5	590	4523.60	100	452360
500	2562/0.5	660	5734.50	100	573450
630	3416/0.5	725	7655.55	100	765555

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1860	1910	2205
1	32/0.2	180	2415	2470	2865
1.5	30/0.25	180	3415	3505	3995
2.5	50/0.25	180	5900	6025	6570
4	56/0.3	180	9025	9195	9745
6	84/0.3	180	12940	13130	13865
10	140/0.3	100	12770	12855	13875
16	126/0.4	100	20120	20230	21695
25	196/0.4	100	30815	30990	33185
35	276/0.4	100	43065	43275	46130

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4745
4	56/0.3	6850
6	84/0.3	9570
10	140/0.3	15625
16	126/0.4	23710

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	2005	2610	3295
0.75	2620	3505	4435
1	3295	4450	5715
1.5	4425	6020	7885
2.5	6990	9630	12485
4	10680	14915	19450
6	15570	21850	28710
10	25735	36570	47830
16	41350	58140	76380
25	61305	88580	116815
35	85410	122725	161985

Paramount Flat Three Core <i>PVC / XLPE</i> Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core <i>PVC</i>	3 core <i>XLPE</i>
	Rate Per 1000 meter	Rate Per 1000 meter
1	44485	45695
1.5	63375	64520
2.5	99685	101230
4	145535	146685
6	211835	212980
10	354250	357555
16	564290	560550
25	863160	861270
35	1190520	1192735

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4165	4985	5420	6605	8110	9320	10785	12230	14140	18410
0.75	5665	6890	7570	9005	11230	12985	14880	17065	19815	25660
1	7495	8985	9890	11785	14695	17030	19550	22400	26240	33960
1.5	10185	12215	13565	16225	20060	23375	27090	30830	36180	46680
2.5	16110	19520	21790	25925	32305	37770	43550	49830	58270	75015
4	25150

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity. Cable in XLPE insulation will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.