

**Paramount LFFR-PVC Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	825
1	14/0.3	16	1140
1.5	22/0.3	12	1645
2.5	50/0.25	8	2670
4	56/0.3	6	4045
6	84/0.3	4	5955

**Paramount LFFR Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.25	180	1125
0.75	24/0.2	8	9.00	180	1620
1	32/0.2	13	11.58	180	2085
1.5	30/0.25	17	16.94	180	3050
2.5	50/0.25	24	27.44	180	4940
4	56/0.3	30	43.50	180	7830
6	84/0.3	38	64.06	180	11530
10	140/0.3	52	110.20	100	11020
16	126/0.4	70	175.20	100	17520
25	196/0.4	88	272.15	100	27215
35	276/0.4	112	380.95	100	38095
50	396/0.4	146	546.25	100	54625
70	360/0.5	216	795.00	100	79500
95	480/0.5	262	1030.35	100	103035
120	608/0.5	310	1314.05	100	131405
150	750/0.5	355	1639.10	100	163910
185	931/0.5	415	1995.20	100	199520
240	1200/0.5	500	2638.90	100	263890
300	1500/0.5	550	3294.95	100	329495
400	2013/0.5	590	4342.65	100	434265
500	2562/0.5	660	5505.10	100	550510
630	3416/0.5	725	7349.35	100	734935

**Paramount FRLS/HRFR/ZHLS Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1720	1835	2115
1	32/0.2	180	2260	2370	2750
1.5	30/0.25	180	3195	3365	3835
2.5	50/0.25	180	5370	5785	6305
4	56/0.3	180	8440	8825	9355
6	84/0.3	180	12100	12605	13310
10	140/0.3	100	11810	12340	13320
16	126/0.4	100	18810	19420	20825
25	196/0.4	100	28810	29750	31860
35	276/0.4	100	40265	41545	44285

**Paramount SOLAR CABLE-XLPO Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618**

Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4555
4	56/0.3	6575
6	84/0.3	9185
10	140/0.3	15000
16	126/0.4	22760

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	1935	2520	3180
0.75	2530	3380	4280
1	3180	4295	5515
1.5	4270	5810	7610
2.5	6745	9295	12050
4	10305	14395	18770
6	15025	21085	27705
10	24835	35290	46155
16	39905	56105	73705
25	59160	85480	112725
35	82420	118430	156315

Paramount Flat Three Core <i>PVC / XLPE</i> Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core <i>PVC</i>	3 core <i>XLPE</i>
	Rate Per 1000 meter	Rate Per 1000 meter
1	42930	44095
1.5	61155	62260
2.5	96195	97685
4	140440	143020
6	204420	207655
10	341850	345040
16	544540	540930
25	832950	831125
35	1148850	1150990

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4020	4810	5230	6375	7825	8995	10410	11800	13645	17765
0.75	5465	6650	7305	8690	10835	12530	14360	16470	19120	24760
1	7235	8670	9545	11375	14180	16435	18865	21615	25320	32770
1.5	9830	11785	13090	15655	19360	22555	26140	29750	34915	45045
2.5	15545	18835	21025	25020	31175	36450	42025	48085	56230	72390
4	24270	....	....	....	....	....	....	....	....	....

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity. Cable in XLPE insulation will not bear any ISI mark on the cable and drums.

**Terms & Conditions:**

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.