

**Paramount LFFR-PVC Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	860
1	14/0.3	16	1185
1.5	22/0.3	12	1710
2.5	50/0.25	8	2775
4	56/0.3	6	4205
6	84/0.3	4	6195

**Paramount LFFR Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.50	180	1170
0.75	24/0.2	8	9.36	180	1685
1	32/0.2	13	12.06	180	2170
1.5	30/0.25	17	17.61	180	3170
2.5	50/0.25	24	28.56	180	5140
4	56/0.3	30	45.25	180	8145
6	84/0.3	38	66.61	180	11990
10	140/0.3	52	114.60	100	11460
16	126/0.4	70	182.20	100	18220
25	196/0.4	88	283.05	100	28305
35	276/0.4	112	396.20	100	39620
50	396/0.4	146	568.10	100	56810
70	360/0.5	216	826.80	100	82680
95	480/0.5	262	1071.55	100	107155
120	608/0.5	310	1366.60	100	136660
150	750/0.5	355	1704.65	100	170465
185	931/0.5	415	2075.00	100	207500
240	1200/0.5	500	2744.45	100	274445
300	1500/0.5	550	3426.75	100	342675
400	2013/0.5	590	4516.35	100	451635
500	2562/0.5	660	5725.30	100	572530
630	3416/0.5	725	7643.30	100	764330

**Paramount FRLS/HRFR/ZHLS Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1790	1910	2200
1	32/0.2	180	2350	2465	2860
1.5	30/0.25	180	3325	3500	3990
2.5	50/0.25	180	5585	6015	6555
4	56/0.3	180	8780	9180	9730
6	84/0.3	180	12585	13110	13840
10	140/0.3	100	12280	12835	13855
16	126/0.4	100	19560	20195	21660
25	196/0.4	100	29960	30940	33135
35	276/0.4	100	41875	43205	46055

**Paramount SOLAR CABLE-XLPO Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618**

Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4735
4	56/0.3	6840
6	84/0.3	9550
10	140/0.3	15600
16	126/0.4	23670

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	2010	2620	3305
0.75	2630	3515	4450
1	3305	4465	5735
1.5	4440	6040	7915
2.5	7015	9665	12530
4	10715	14970	19520
6	15625	21930	28815
10	25830	36700	48000
16	41500	58350	76655
25	61525	88900	117235
35	85715	123165	162570

Paramount Flat Three Core <i>PVC / XLPE</i> Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core <i>PVC</i>	3 core <i>XLPE</i>
	Rate Per 1000 meter	Rate Per 1000 meter
1	44645	45860
1.5	63600	64750
2.5	100045	101590
4	146060	148740
6	212595	215960
10	355525	358840
16	566320	562565
25	866270	864370
35	1194805	1197030

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4180	5000	5440	6630	8140	9355	10825	12270	14190	18475
0.75	5685	6915	7595	9040	11270	13030	14935	17130	19885	25750
1	7525	9015	9925	11830	14745	17090	19620	22480	26335	34080
1.5	10225	12255	13615	16280	20135	23455	27185	30940	36310	46845
2.5	16165	19590	21865	26020	32420	37910	43705	50010	58480	75285
4	25240	....	....	....	....	....	....	....	....	....

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity. Cable in XLPE insulation will not bear any ISI mark on the cable and drums.

**Terms & Conditions:**

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.