

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	20	860
1	14/0.3	16	1190
1.5	22/0.3	12	1710
2.5	50/0.25	8	2780
4	56/0.3	6	4210
6	84/0.3	4	6200

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.47	180	1165
0.75	24/0.2	8	9.33	180	1680
1	32/0.2	13	12.03	180	2165
1.5	30/0.25	17	17.56	180	3160
2.5	50/0.25	24	28.42	180	5115
4	56/0.3	30	45.14	180	8125
6	84/0.3	38	66.33	180	11940
10	140/0.3	52	114.10	100	11410
16	126/0.4	70	181.40	100	18140
25	196/0.4	88	281.75	100	28175
35	276/0.4	112	394.35	100	39435
50	396/0.4	146	565.50	100	56550
70	360/0.5	216	823.05	100	82305
95	480/0.5	262	1066.65	100	106665
120	608/0.5	310	1360.35	100	136035
150	750/0.5	355	1696.85	100	169685
185	931/0.5	415	2065.55	100	206555
240	1200/0.5	500	2731.90	100	273190
300	1500/0.5	550	3411.10	100	341110
400	2013/0.5	590	4495.75	100	449575
500	2562/0.5	660	5699.20	100	569920
630	3416/0.5	725	7608.35	100	760835

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1845	1895	2190
1	32/0.2	180	2400	2455	2845
1.5	30/0.25	180	3395	3480	3970
2.5	50/0.25	180	5860	5990	6530
4	56/0.3	180	8970	9140	9685
6	84/0.3	180	12860	13050	13780
10	140/0.3	100	12690	12775	13790
16	126/0.4	100	19995	20110	21560
25	196/0.4	100	30625	30800	32980
35	276/0.4	100	42800	43010	45845

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per TUV 2Pfg 1169/08.2007		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4720
4	56/0.3	6810
6	84/0.3	9515
10	140/0.3	15530
16	126/0.4	23565

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	2005	2610	3295
0.75	2620	3505	4435
1	3295	4455	5715
1.5	4425	6025	7890
2.5	6995	9635	12495
4	10690	14925	19465
6	15585	21865	28730
10	25755	36595	47865
16	41385	58185	76435
25	61350	88650	116905
35	85475	122815	162110

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	44210	45415
1.5	62985	64125
2.5	99070	100605
4	144635	145780
6	210530	211665
10	352065	355355
16	560815	557095
25	857840	855965
35	1183185	1185385

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4200	5025	5465	6660	8175	9395	10875	12330	14255	18560
0.75	5710	6945	7630	9080	11320	13090	15005	17205	19975	25865
1	7560	9060	9970	11880	14810	17165	19705	22580	26450	34235
1.5	10265	12315	13675	16355	20220	23565	27310	31080	36475	47060
2.5	16240	19675	21970	26135	32565	38075	43900	50235	58740	75625
4	25350

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity. Cable in XLPE insulation will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.