

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	870
1	14/0.3	16	1210
1.5	22/0.3	12	1730
2.5	50/0.25	8	2810
4	56/0.3	6	4255
6	84/0.3	4	6265

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.53	180	1175
0.75	24/0.2	8	9.39	180	1690
1	32/0.2	13	12.11	180	2180
1.5	30/0.25	17	17.67	180	3180
2.5	50/0.25	24	28.67	180	5160
4	56/0.3	30	45.42	180	8175
6	84/0.3	38	66.86	180	12035
10	140/0.3	52	115.00	100	11500
16	126/0.4	70	182.85	100	18285
25	196/0.4	88	284.10	100	28410
35	276/0.4	112	397.65	100	39765
50	396/0.4	146	570.15	100	57015
70	360/0.5	216	829.75	100	82975
95	480/0.5	262	1075.40	100	107540
120	608/0.5	310	1371.50	100	137150
150	750/0.5	355	1710.80	100	171080
185	931/0.5	415	2082.50	100	208250
240	1200/0.5	500	2754.35	100	275435
300	1500/0.5	550	3439.05	100	343905
400	2013/0.5	590	4532.65	100	453265
500	2562/0.5	660	5745.90	100	574590
630	3416/0.5	725	7670.85	100	767085

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1795	1920	2210
1	32/0.2	180	2360	2475	2870
1.5	30/0.25	180	3340	3515	4005
2.5	50/0.25	180	5605	6035	6580
4	56/0.3	180	8815	9215	9765
6	84/0.3	180	12630	13155	13890
10	140/0.3	100	12325	12880	13905
16	126/0.4	100	19630	20270	21735
25	196/0.4	100	30065	31050	33255
35	276/0.4	100	42025	43365	46225

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4755
4	56/0.3	6865
6	84/0.3	9585
10	140/0.3	15655
16	126/0.4	23755

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	2020	2630	3320
0.75	2640	3525	4465
1	3320	4480	5755
1.5	4455	6065	7945
2.5	7040	9700	12575
4	10755	15025	19590
6	15685	22005	28915
10	25920	36830	48175
16	41650	58560	76930
25	61745	89220	117655
35	86025	123610	163155

Paramount Flat Three Core <i>PVC / XLPE</i> Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core <i>PVC</i>	3 core <i>XLPE</i>
	Rate Per 1000 meter	Rate Per 1000 meter
1	44805	46025
1.5	63830	64985
2.5	100405	101955
4	146590	149275
6	213360	216735
10	356805	360130
16	568360	564590
25	869390	867480
35	1199105	1201340

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4195	5020	5460	6655	8170	9390	10865	12315	14245	18545
0.75	5705	6940	7625	9075	11310	13080	14985	17190	19960	25845
1	7550	9050	9965	11870	14800	17150	19690	22565	26430	34200
1.5	10260	12300	13665	16340	20205	23540	27285	31050	36440	47015
2.5	16225	19660	21945	26115	32535	38050	43860	50190	58690	75555
4	25330

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity. Cable in XLPE insulation will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.