

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	840
1	14/0.3	16	1160
1.5	22/0.3	12	1670
2.5	50/0.25	8	2710
4	56/0.3	6	4105
6	84/0.3	4	6050

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.31	180	1135
0.75	24/0.2	8	9.06	180	1630
1	32/0.2	13	11.67	180	2100
1.5	30/0.25	17	17.08	180	3075
2.5	50/0.25	24	27.67	180	4980
4	56/0.3	30	43.83	180	7890
6	84/0.3	38	64.56	180	11620
10	140/0.3	52	111.05	100	11105
16	126/0.4	70	176.50	100	17650
25	196/0.4	88	274.20	100	27420
35	276/0.4	112	383.90	100	38390
50	396/0.4	146	550.35	100	55035
70	360/0.5	216	801.00	100	80100
95	480/0.5	262	1038.15	100	103815
120	608/0.5	310	1323.95	100	132395
150	750/0.5	355	1651.50	100	165150
185	931/0.5	415	2010.35	100	201035
240	1200/0.5	500	2658.85	100	265885
300	1500/0.5	550	3319.85	100	331985
400	2013/0.5	590	4375.50	100	437550
500	2562/0.5	660	5546.70	100	554670
630	3416/0.5	725	7404.95	100	740495

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1735	1855	2130
1	32/0.2	180	2275	2390	2770
1.5	30/0.25	180	3225	3395	3865
2.5	50/0.25	180	5415	5825	6350
4	56/0.3	180	8510	8895	9430
6	84/0.3	180	12190	12700	13410
10	140/0.3	100	11895	12435	13425
16	126/0.4	100	18950	19565	20985
25	196/0.4	100	29025	29975	32100
35	276/0.4	100	40570	41860	44620

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4590
4	56/0.3	6625
6	84/0.3	9255
10	140/0.3	15115
16	126/0.4	22930

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	1945	2540	3205
0.75	2550	3405	4310
1	3205	4325	5560
1.5	4300	5855	7670
2.5	6795	9360	12135
4	10380	14500	18910
6	15140	21245	27915
10	25020	35555	46505
16	40210	56530	74260
25	59605	86130	113575
35	83045	119325	157500

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	43255	44425
1.5	61620	62730
2.5	96930	98425
4	141505	144105
6	205965	209225
*8	283600	285095
10	344440	347645
16	548660	545020
25	839250	837410
35	1157540	1159695

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4050	4845	5275	6425	7885	9065	10485	11885	13750	17900
0.75	5505	6700	7360	8760	10920	12625	14470	16595	19265	24950
1	7285	8735	9620	11465	14290	16555	19010	21780	25520	33015
1.5	9905	11870	13190	15775	19505	22725	26340	29975	35180	45385
2.5	15660	18980	21180	25205	31405	36725	42340	48450	56655	72935
4	24450									

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- 1.The above rates are exclusive of GST which shall be charged extra at actual.
- 2.Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- 3.This Price List is subject to change without prior notice.
- 4.As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
5. This price list supersedes our previous list.