

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	905
1	14/0.3	16	1250
1.5	22/0.3	12	1795
2.5	50/0.25	8	2915
4	56/0.3	6	4420
6	84/0.3	4	6510

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	6.81	180	1225
0.75	24/0.2	8	9.75	180	1755
1	32/0.2	13	12.56	180	2260
1.5	30/0.25	17	18.39	180	3310
2.5	50/0.25	24	29.78	180	5360
4	56/0.3	30	47.17	180	8490
6	84/0.3	38	69.50	180	12510
10	140/0.3	52	119.50	100	11950
16	126/0.4	70	190.00	100	19000
25	196/0.4	88	295.15	100	29515
35	276/0.4	112	413.20	100	41320
50	396/0.4	146	592.40	100	59240
70	360/0.5	216	862.20	100	86220
95	480/0.5	262	1117.40	100	111740
120	608/0.5	310	1425.05	100	142505
150	750/0.5	355	1777.65	100	177765
185	931/0.5	415	2163.90	100	216390
240	1200/0.5	500	2861.95	100	286195
300	1500/0.5	550	3573.45	100	357345
400	2013/0.5	590	4709.70	100	470970
500	2562/0.5	660	5970.40	100	597040
630	3416/0.5	725	7970.55	100	797055

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	1870	2000	2290
1	32/0.2	180	2445	2570	2985
1.5	30/0.25	180	3470	3655	4160
2.5	50/0.25	180	5830	6270	6835
4	56/0.3	180	9160	9575	10150
6	84/0.3	180	13125	13670	14435
10	140/0.3	100	12805	13385	14450
16	126/0.4	100	20395	21060	22585
25	196/0.4	100	31245	32265	34555
35	276/0.4	100	43670	45060	48025

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	4940
4	56/0.3	7130
6	84/0.3	9965
10	140/0.3	16265
16	126/0.4	24680

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	2095	2735	3450
0.75	2745	3665	4640
1	3450	4655	5985
1.5	4630	6305	8255
2.5	7315	10075	13060
4	11170	15605	20355
6	16300	22870	30045
10	26935	38270	50055
16	43280	60850	79930
25	64160	92710	122250
35	89390	128440	169530

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	46560	47820
1.5	66330	67520
2.5	104335	105945
4	152315	155110
6	221700	225205
*8	305265	306870
10	370750	374200
16	590570	586650
25	903355	901375
35	1245955	1248270

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	4355	5215	5680	6920	8485	9755	11285	12795	14800	19265
0.75	5925	7210	7925	9425	11755	13590	15575	17860	20740	26855
1	7840	9400	10355	12340	15380	17820	20465	23445	27470	35540
1.5	10660	12775	14195	16980	20995	24460	28350	32265	37865	48855
2.5	16855	20430	22800	27130	33805	39530	45575	52150	60985	78505
4	26320

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- 1.The above rates are exclusive of GST which shall be charged extra at actual.
- 2.Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- 3.This Price List is subject to change without prior notice.
- 4.As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
5. This price list supersedes our previous list.