

Paramount LFFR-PVC Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1230
1	14/0.3	16	1725
1.5	22/0.3	12	2475
2.5	50/0.25	8	3925
4	56/0.3	6	5970
6	84/0.3	4	8805

Paramount LFFR Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	9.31	180	1675
0.75	24/0.2	8	13.28	180	2390
1	32/0.2	13	17.28	180	3110
1.5	30/0.25	17	25.06	180	4510
2.5	50/0.25	24	40.22	180	7240
4	56/0.3	30	63.78	180	11480
6	84/0.3	38	93.94	180	16910
10	140/0.3	52	163.05	100	16305
16	126/0.4	70	256.85	100	25685
25	196/0.4	88	398.95	100	39895
35	276/0.4	112	558.55	100	55855
50	396/0.4	146	800.70	100	80070
70	360/0.5	216	1165.40	100	116540
95	480/0.5	262	1510.15	100	151015
120	608/0.5	310	1925.95	100	192595
150	750/0.5	355	2402.55	100	240255
185	931/0.5	415	2924.55	100	292455
240	1200/0.5	500	3868.10	100	386810
300	1500/0.5	550	4829.65	100	482965
400	2013/0.5	590	6365.30	100	636530
500	2562/0.5	660	8069.20	100	806920
630	3416/0.5	725	10772.55	100	1077255

Paramount FRLS/HRFR/ZHLS Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	2530	2705	3085
1	32/0.2	180	3310	3470	4040
1.5	30/0.25	180	4685	4940	5620
2.5	50/0.25	180	7810	8385	9155
4	56/0.3	180	12255	12825	13585
6	84/0.3	180	17565	18290	19315
10	140/0.3	100	17145	17910	19335
16	126/0.4	100	27300	28190	30240
25	196/0.4	100	41830	43185	46245
35	276/0.4	100	58455	60320	64290

Paramount SOLAR CABLE-XLPO Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618

Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	6610
4	56/0.3	9545
6	84/0.3	13335
10	140/0.3	21770
16	126/0.4	33040

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	2835	3700	4660
0.75	3715	4945	6270
1	4760	6420	8220
1.5	6365	8660	11340
2.5	9890	13620	17650
4	15090	21085	27520
6	22030	30915	40610
10	36405	51720	67650
16	58490	82245	108030
25	86705	125300	165220
35	120815	173595	229130

Paramount Flat Three Core <i>PVC / XLPE</i> Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core <i>PVC</i>	3 core <i>XLPE</i>
	Rate Per 1000 meter	Rate Per 1000 meter
1	63385	65105
1.5	90295	91930
2.5	142030	144230
4	207345	211155
6	301805	306570
*8	415560	417755
10	504700	509405
16	803950	798630
25	1229755	1227060
35	1696145	1699290

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	5880	7050	7670	9355	11475	13185	15245	17295	20000	26035
0.75	8005	9745	10710	12735	15885	18370	21055	24150	28040	36290
1	10605	12710	14000	16675	20795	24085	27655	31685	37130	48035
1.5	14395	17275	19190	22955	28370	33060	38320	43615	51170	66025
2.5	22775	27605	30810	36660	45685	53425	61600	70480	82420	106100
4	35575

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.