

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1305
1	14/0.3	16	1835
1.5	22/0.3	12	2635
2.5	50/0.25	8	4160
4	56/0.3	6	6325
6	84/0.3	4	9325

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	9.86	180	1775
0.75	24/0.2	8	14.06	180	2530
1	32/0.2	13	18.42	180	3315
1.5	30/0.25	17	26.53	180	4775
2.5	50/0.25	24	42.78	180	7700
4	56/0.3	30	67.86	180	12215
6	84/0.3	38	99.94	180	17990
10	140/0.3	52	172.70	100	17270
16	126/0.4	70	272.00	100	27200
25	196/0.4	88	422.50	100	42250
35	276/0.4	112	591.50	100	59150
50	396/0.4	146	847.95	100	84795
70	360/0.5	216	1234.20	100	123420
95	480/0.5	262	1599.35	100	159935
120	608/0.5	310	2039.70	100	203970
150	750/0.5	355	2544.45	100	254445
185	931/0.5	415	3097.25	100	309725
240	1200/0.5	500	4096.50	100	409650
300	1500/0.5	550	5114.80	100	511480
400	2013/0.5	590	6741.15	100	674115
500	2562/0.5	660	8545.70	100	854570
630	3416/0.5	725	11408.65	100	1140865

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	2675	2860	3270
1	32/0.2	180	3505	3675	4280
1.5	30/0.25	180	4960	5235	5950
2.5	50/0.25	180	8275	8880	9695
4	56/0.3	180	12985	13585	14390
6	84/0.3	180	18600	19370	20455
10	140/0.3	100	18160	18965	20475
16	126/0.4	100	28910	29850	32025
25	196/0.4	100	44300	45735	48975
35	276/0.4	100	61910	63885	68090

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	7005
4	56/0.3	10105
6	84/0.3	14125
10	140/0.3	23055
16	126/0.4	34990

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	3000	3920	4935
0.75	3935	5240	6645
1	5045	6800	8705
1.5	6740	9170	12010
2.5	10470	14425	18690
4	15985	22335	29145
6	23330	32740	43010
10	38555	54770	71645
16	61945	87100	114405
25	91825	132700	174975
35	127950	183850	242660

Paramount Flat Three Core <i>PVC / XLPE</i> Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core <i>PVC</i>	3 core <i>XLPE</i>
	Rate Per 1000 meter	Rate Per 1000 meter
1	67125	68950
1.5	95625	97360
2.5	150415	152745
4	221660	225735
6	322640	327735
*8	444245	446600
10	539545	544575
16	851420	845785
25	1302370	1299510
35	1796295	1799625

Paramount <i>PVC</i> Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	6225	7465	8125	9910	12155	13965	16140	18320	21180	27570
0.75	8480	10315	11340	13485	16820	19455	22295	25580	29695	38435
1	11235	13460	14825	17660	22025	25510	29290	33555	39325	50870
1.5	15245	18300	20320	24315	30045	35010	40585	46190	54190	69920
2.5	24125	29235	32630	38825	48385	56580	65235	74640	87290	112365
4	37675

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.