

Paramount LFFR-PVC Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1360
1	32/0.2	16	1840
1.5	30/0.25	12	2635
2.5	50/0.25	8	4355
4	56/0.3	6	6615
6	84/0.3	4	9755

Paramount LFFR Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	10.53	200	2105
0.75	24/0.2	8	14.97	180	2695
1	32/0.2	13	19.75	180	3555
1.5	30/0.25	17	28.42	180	5115
2.5	50/0.25	24	45.56	180	8200
4	56/0.3	30	72.31	180	13015
6	84/0.3	38	106.56	180	19180
10	140/0.3	52	184.15	100	18415
16	126/0.4	70	290.00	100	29000
25	196/0.4	88	450.40	100	45040
35	276/0.4	112	630.45	100	63045
50	396/0.4	146	903.90	100	90390
70	360/0.5	216	1315.50	100	131550
95	480/0.5	262	1704.75	100	170475
120	608/0.5	310	2174.20	100	217420
150	750/0.5	355	2712.10	100	271210
185	931/0.5	415	3301.45	100	330145
240	1200/0.5	500	4366.55	100	436655
300	1500/0.5	550	5451.95	100	545195
400	2013/0.5	590	7185.50	100	718550
500	2562/0.5	660	9108.90	100	910890
630	3416/0.5	725	12160.65	100	1216065

Paramount FRLS/HRFR/ZHLS Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HRFR
0.75	24/0.2	180	2850	3050	3485
1	32/0.2	180	3760	3940	4590
1.5	30/0.25	180	5320	5605	6380
2.5	50/0.25	180	8820	9465	10340
4	56/0.3	180	13835	14480	15335
6	84/0.3	180	19825	20645	21810
10	140/0.3	100	19365	20215	21825
16	126/0.4	100	30820	31830	34135
25	196/0.4	100	47225	48750	52205
35	276/0.4	100	65990	68100	72590

Paramount SOLAR CABLE-XLPO Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	7470
4	56/0.3	10760
6	84/0.3	15060
10	140/0.3	24570
16	126/0.4	37300

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	3190	4175	5255
0.75	4190	5580	7080
1	5385	7245	9280
1.5	7175	9770	12800
2.5	11170	15375	19925
4	17030	23800	31070
6	24865	34900	45845
10	41100	58380	76360
16	66030	92845	121935
25	97880	141455	186510
35	136385	195960	258655

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	71555	73500
1.5	101925	103775
2.5	160325	162810
4	236285	240615
6	343905	349335
*8	473520	476035
10	575100	580475
16	907535	901530
25	1388215	1385160
35	1914690	1918245

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	6640	7970	8655	10560	12965	14885	17200	19535	22585	29380
0.75	9045	11000	12090	14375	17925	20740	23765	27265	31655	40970
1	11970	14345	15805	18830	23475	27185	31220	35765	41900	54235
1.5	16255	19510	21660	25920	32030	37315	43265	49230	57765	74540
2.5	25715	31155	34780	41370	51575	60315	69545	79560	93045	119770
4	40150									

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

1.The above rates are exclusive of GST which shall be charged extra at actual.

2.Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR

3.This Price List is subject to change without prior notice.

4.As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.

5. This price list supersedes our previous list.