

Paramount LFFR-PVC Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1560
1	32/0.2	16	2110
1.5	30/0.25	12	3025
2.5	50/0.25	8	5000
4	56/0.3	6	7590
6	84/0.3	4	11195

Paramount LFFR Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	12.20	200	2440
0.75	24/0.2	8	17.33	180	3120
1	32/0.2	13	22.89	180	4120
1.5	30/0.25	17	32.94	180	5930
2.5	50/0.25	24	52.78	180	9500
4	56/0.3	30	83.75	180	15075
6	84/0.3	38	123.44	180	22220
10	140/0.3	52	213.25	100	21325
16	126/0.4	70	335.90	100	33590
25	196/0.4	88	521.70	100	52170
35	276/0.4	112	730.25	100	73025
50	396/0.4	146	1046.95	100	104695
70	360/0.5	216	1523.70	100	152370
95	480/0.5	262	1974.60	100	197460
120	608/0.5	310	2518.40	100	251840
150	750/0.5	355	3141.35	100	314135
185	931/0.5	415	3824.05	100	382405
240	1200/0.5	500	5057.80	100	505780
300	1500/0.5	550	6314.90	100	631490
400	2013/0.5	590	8322.90	100	832290
500	2562/0.5	660	10550.70	100	1055070
630	3416/0.5	725	14085.55	100	1408555

Paramount FRLS/HRFR/ZHLS Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HRFR
0.75	24/0.2	180	3245	3290	3370
1	32/0.2	180	4285	4340	4445
1.5	30/0.25	180	6130	6225	6370
2.5	50/0.25	180	9835	9970	10210
4	56/0.3	180	15530	15830	16125
6	84/0.3	180	22885	23325	23765
10	140/0.3	100	21970	22395	22815
16	126/0.4	100	34605	35270	35935
25	196/0.4	100	53740	54780	55815
35	276/0.4	100	75220	76670	78120

Paramount SOLAR CABLE-XLPO Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	8575
4	56/0.3	12355
6	84/0.3	17280
10	140/0.3	28185
16	126/0.4	42800

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	2 core Rate per 100 meter	3 core Rate per 100 meter	4 core Rate per 100 meter
0.5	3660	4795	6025
0.75	4810	6395	8120
1	6175	8310	10645
1.5	8230	11210	14685
2.5	12815	17640	22865
4	19535	27310	35650
6	28530	40040	52600
10	47160	66985	87610
16	75760	106530	139905
25	112305	162300	213995
35	156480	224835	296765

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010		
Size (sq mm)	3 core PVC Rate Per 1000 meter	3 core XLPE Rate Per 1000 meter
1	82095	84330
1.5	116950	119070
2.5	183955	186800
4	271105	276075
6	394580	400815
*8	543295	546185
10	659850	666015
16	1041275	1034380
25	1592785	1589280
35	2196845	2200920

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010										
SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	7620	9145	9930	12110	14880	17080	19730	22410	25920	33710
0.75	10380	12620	13875	16495	20570	23795	27270	31290	36325	47010
1	13735	16460	18140	21605	26935	31190	35820	41040	48075	62225
1.5	18650	22385	24855	29740	36750	42820	49640	56480	66280	85525
2.5	29505	35745	39905	47465	59175	69205	79795	91280	106755	137420
4	46070									

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

1.The above rates are exclusive of GST which shall be charged extra at actual.

2.Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR

3.This Price List is subject to change without prior notice.

4.As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.

5. This price list supersedes our previous list.