

Paramount LFFR-PVC Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1485
1	32/0.2	16	2010
1.5	30/0.25	12	2880
2.5	50/0.25	8	4760
4	56/0.3	6	7215
6	84/0.3	4	10650

Paramount LFFR Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	11.73	200	2345
0.75	24/0.2	8	16.61	180	2990
1	32/0.2	13	21.94	180	3950
1.5	30/0.25	17	31.56	180	5680
2.5	50/0.25	24	50.58	180	9105
4	56/0.3	30	80.31	180	14455
6	84/0.3	38	118.36	180	21305
10	140/0.3	52	204.40	100	20440
16	126/0.4	70	322.05	100	32205
25	196/0.4	88	500.15	100	50015
35	276/0.4	112	700.10	100	70010
50	396/0.4	146	1003.65	100	100365
70	360/0.5	216	1460.70	100	146070
95	480/0.5	262	1893.05	100	189305
120	608/0.5	310	2414.30	100	241430
150	750/0.5	355	3011.55	100	301155
185	931/0.5	415	3666.05	100	366605
240	1200/0.5	500	4848.80	100	484880
300	1500/0.5	550	6053.90	100	605390
400	2013/0.5	590	7978.95	100	797895
500	2562/0.5	660	10114.65	100	1011465
630	3416/0.5	725	13503.40	100	1350340

Paramount FRLS/HRFR/ZHLS Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFFR
0.75	24/0.2	180	3110	3155	3230
1	32/0.2	180	4110	4160	4265
1.5	30/0.25	180	5875	5970	6110
2.5	50/0.25	180	9430	9555	9785
4	56/0.3	180	14890	15175	15460
6	84/0.3	180	21940	22360	22790
10	140/0.3	100	21065	21470	21870
16	126/0.4	100	33180	33815	34455
25	196/0.4	100	51520	52520	53510
35	276/0.4	100	72105	73500	74890

Paramount SOLAR CABLE-XLPO Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	8220
4	56/0.3	11845
6	84/0.3	16560
10	140/0.3	27020
16	126/0.4	41025

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	3470	4555	5710
0.75	4565	6060	7705
1	5855	7890	10100
1.5	7800	10635	13935
2.5	12160	16740	21690
4	18535	25910	33825
6	27075	37980	49910
10	44745	63555	83125
16	71885	101070	132735
25	106560	153990	203035
35	148475	213320	281565

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	78705	80845
1.5	112120	114145
2.5	176350	179080
4	259905	264665
6	378275	384245
*8	520840	523615
10	632575	638490
16	998240	991625
25	1526965	1523595
35	2106055	2109960

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	7230	8685	9425	11490	14115	16200	18715	21260	24595	31980
0.75	9840	11980	13170	15650	19520	22585	25870	29685	34465	44605
1	13030	15615	17210	20500	25560	29590	33985	38945	45615	59035
1.5	17690	21240	23585	28215	34870	40630	47095	53590	62890	81145
2.5	27995	33915	37860	45035	56145	65665	75710	86610	101290	130390
4	43710		

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.