

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1490
1	32/0.2	16	2020
1.5	30/0.25	12	2890
2.5	50/0.25	8	4780
4	56/0.3	6	7205
6	84/0.3	4	10640

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	11.73	200	2345
0.75	24/0.2	8	16.61	180	2990
1	32/0.2	13	21.94	180	3950
1.5	30/0.25	17	31.53	180	5675
2.5	50/0.25	24	50.56	180	9100
4	56/0.3	30	80.25	180	14445
6	84/0.3	38	118.25	180	21285
10	140/0.3	52	204.25	100	20425
16	126/0.4	70	321.75	100	32175
25	196/0.4	88	499.70	100	49970
35	276/0.4	112	699.45	100	69945
50	396/0.4	146	1002.75	100	100275
70	360/0.5	216	1459.35	100	145935
95	480/0.5	262	1891.35	100	189135
120	608/0.5	310	2412.15	100	241215
150	750/0.5	355	3008.85	100	300885
185	931/0.5	415	3662.75	100	366275
240	1200/0.5	500	4844.40	100	484440
300	1500/0.5	550	6048.45	100	604845
400	2013/0.5	590	7971.75	100	797175
500	2562/0.5	660	10105.55	100	1010555
630	3416/0.5	725	13491.25	100	1349125

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFFR
0.75	24/0.2	180	3110	3155	3225
1	32/0.2	180	4110	4155	4265
1.5	30/0.25	180	5870	5965	6105
2.5	50/0.25	180	9425	9545	9780
4	56/0.3	180	14875	15160	15445
6	84/0.3	180	21920	22340	22770
10	140/0.3	100	21045	21450	21850
16	126/0.4	100	33150	33785	34425
25	196/0.4	100	51475	52470	53460
35	276/0.4	100	72040	73435	74820

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	8210
4	56/0.3	11835
6	84/0.3	16545
10	140/0.3	26995
16	126/0.4	40985

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	3505	4595	5760
0.75	4605	6115	7775
1	5910	7965	10195
1.5	7875	10735	14070
2.5	12275	16895	21895
4	18710	26150	34145
6	27325	38340	50375
10	45165	64150	83910
16	72560	102020	133980
25	107560	155440	204945
35	149870	215325	284210

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	79040	81190
1.5	112600	114630
2.5	177100	179840
4	261010	265790
6	379885	385875
*8	523055	525840
10	635260	641205
16	1002480	995840
25	1533455	1530070
35	2115005	2118930

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	7295	8765	9515	11600	14250	16350	18890	21460	24830	32280
0.75	9930	12095	13295	15800	19705	22800	26110	29965	34790	45025
1	13150	15765	17370	20695	25800	29870	34305	39315	46045	59590
1.5	17855	21440	23810	28480	35195	41015	47540	54095	63480	81910
2.5	28260	34230	38215	45455	56675	66280	76420	87425	102245	131615
4	44120		

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.