

Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010			
Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1565
1	32/0.2	16	2120
1.5	30/0.25	12	3040
2.5	50/0.25	8	5020
4	56/0.3	6	7570
6	84/0.3	4	11180

Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	12.30	200	2460
0.75	24/0.2	8	17.44	180	3140
1	32/0.2	13	23.06	180	4150
1.5	30/0.25	17	33.14	180	5965
2.5	50/0.25	24	53.11	180	9560
4	56/0.3	30	84.31	180	15175
6	84/0.3	38	124.22	180	22360
10	140/0.3	52	214.60	100	21460
16	126/0.4	70	338.05	100	33805
25	196/0.4	88	525.00	100	52500
35	276/0.4	112	734.85	100	73485
50	396/0.4	146	1053.50	100	105350
70	360/0.5	216	1533.20	100	153320
95	480/0.5	262	1987.10	100	198710
120	608/0.5	310	2534.20	100	253420
150	750/0.5	355	3161.10	100	316110
185	931/0.5	415	3848.10	100	384810
240	1200/0.5	500	5089.55	100	508955
300	1500/0.5	550	6354.50	100	635450
400	2013/0.5	590	8375.15	100	837515
500	2562/0.5	660	10616.90	100	1061690
630	3416/0.5	725	14173.95	100	1417395

Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010					
Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFFR
0.75	24/0.2	180	3265	3315	3390
1	32/0.2	180	4315	4365	4480
1.5	30/0.25	180	6165	6270	6410
2.5	50/0.25	180	9905	10025	10275
4	56/0.3	180	15630	15930	16230
6	84/0.3	180	23030	23470	23920
10	140/0.3	100	22110	22535	22955
16	126/0.4	100	34830	35495	36170
25	196/0.4	100	54080	55125	56165
35	276/0.4	100	75685	77150	78605

Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618		
Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	8625
4	56/0.3	12430
6	84/0.3	17380
10	140/0.3	28360
16	126/0.4	43060

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	3680	4825	6050
0.75	4835	6420	8170
1	6210	8370	10710
1.5	8275	11280	14780
2.5	12895	17750	23005
4	19660	27475	35875
6	28705	40280	52925
10	47450	67400	88160
16	76230	107180	140760
25	113000	163305	215315
35	157450	226220	298590

Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	83040	85300
1.5	118295	120435
2.5	186060	188940
4	274215	279240
6	399110	405405
*8	549520	552445
10	667405	673650
16	1053205	1046230
25	1611050	1607490
35	2222025	2226150

Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	7665	9210	9995	12185	14970	17175	19850	22545	26085	33915
0.75	10435	12705	13965	16600	20705	23955	27430	31480	36550	47305
1	13815	16560	18245	21745	27105	31380	36040	41305	48375	62605
1.5	18755	22525	25015	29920	36975	43090	49945	56830	66695	86055
2.5	29690	35960	40150	47755	59545	69635	80290	91850	107420	138270
4	46350			

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

Terms & Conditions:

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.