

Paramount **LFFR-PVC** Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	Configuration	Std. pack of coil in carton	Rate per 90 meters
0.75	24/0.2	22	1520
1	32/0.2	16	2060
1.5	30/0.25	12	2950
2.5	50/0.25	8	4875
4	56/0.3	6	7350
6	84/0.3	4	10855

Paramount **LFFR** Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	Configuration	Amps	Rate per meter	Coil Length in meter	Rate per Coil
0.5	16/0.2	5	11.95	200	2390
0.75	24/0.2	8	16.94	180	3050
1	32/0.2	13	22.39	180	4030
1.5	30/0.25	17	32.17	180	5790
2.5	50/0.25	24	51.56	180	9280
4	56/0.3	30	81.86	180	14735
6	84/0.3	38	120.61	180	21710
10	140/0.3	52	208.35	100	20835
16	126/0.4	70	328.20	100	32820
25	196/0.4	88	509.70	100	50970
35	276/0.4	112	713.45	100	71345
50	396/0.4	146	1022.80	100	102280
70	360/0.5	216	1488.55	100	148855
95	480/0.5	262	1929.20	100	192920
120	608/0.5	310	2460.40	100	246040
150	750/0.5	355	3069.05	100	306905
185	931/0.5	415	3736.00	100	373600
240	1200/0.5	500	4941.30	100	494130
300	1500/0.5	550	6169.40	100	616940
400	2013/0.5	590	8131.20	100	813120
500	2562/0.5	660	10307.65	100	1030765
630	3416/0.5	725	13761.10	100	1376110

Paramount **FRLS/HRFR/ZHLS** Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010

Size (sq mm)	Configuration	Coil Length in meter	FRLS	HRFR	ZHLS/HFRF
0.75	24/0.2	180	3170	3220	3290
1	32/0.2	180	4190	4240	4350
1.5	30/0.25	180	5985	6085	6225
2.5	50/0.25	180	9615	9735	9975
4	56/0.3	180	15175	15465	15755
6	84/0.3	180	22360	22785	23225
10	140/0.3	100	21465	21880	22285
16	126/0.4	100	33815	34460	35115
25	196/0.4	100	52505	53520	54530
35	276/0.4	100	73480	74905	76315

Paramount **SOLAR CABLE-XLPO** Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618

Size (sq mm)	Configuration	Rate per 100 meters
2.5	50/0.25	8375
4	56/0.3	12070
6	84/0.3	16875
10	140/0.3	27535
16	126/0.4	41805

**Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	2 core	3 core	4 core
	Rate per 100 meter	Rate per 100 meter	Rate per 100 meter
0.5	3575	4685	5875
0.75	4695	6235	7930
1	6030	8125	10400
1.5	8035	10950	14350
2.5	12520	17235	22335
4	19085	26675	34830
6	27870	39105	51385
10	46070	65435	85590
16	74010	104060	136660
25	109710	158550	209045
35	152865	219630	289895

**Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

Size (sq mm)	3 core PVC	3 core XLPE
	Rate Per 1000 meter	Rate Per 1000 meter
1	80620	82815
1.5	114850	116925
2.5	180640	183435
4	266230	271105
6	387485	393595
*8	533515	536355
10	647965	654030
16	1022530	1015755
25	1564125	1560670
35	2157305	2161310

**Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

SIZE	5 Core	6 Core	7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	7440	8940	9705	11830	14535	16675	19270	21890	25325	32925
0.75	10130	12335	13560	16115	20100	23255	26630	30565	35485	45925
1	13415	16080	17715	21110	26315	30465	34990	40100	46965	60780
1.5	18210	21870	24285	29050	35900	41835	48490	55175	64750	83550
2.5	28825	34915	38980	46365	57810	67605	77950	89175	104290	134245
4	45000				....	....	....	....	....	....

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

\*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

**Terms & Conditions:**

- The above rates are exclusive of GST which shall be charged extra at actual.
- Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- This Price List is subject to change without prior notice.
- As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- This price list supersedes our previous list.